



TRACK MOUNTED CONE TMC AVC SERIES

Propel AVC Series Cone crusher feature a unique combination of crusher speed, throw and cavity design. This combination is known for its revolutionary higher capacity and better product quality. It has been designed to ensure trouble-free operation in heavy and continu-



FEATURES

Heavy duty track unit with dual speed (optional) configuration.

propel

- Safety guards in compliance with machinery directive. Sturdy walkway with handrails,kick board and access ladders.
- Dual power mode flexibility to power the plant either by external electric connection or by on-board diesel generator power pack unit (optional).
- Four-point emergency stop. Detachable dog lead control system for marching.
- Radio remote control for marching (optional). Feed level sensor for crusher (optional).
- Electrical driven hydraulic system for quick setup & marching. Low noise acoustic engine canopy with overload protection.

Propel. Always Ahead.

TECHNICAL DATA

Series		TMC 220	TMC 250	SM 200	SM 250		
Feed Opening	mm (inch)	220 (8.7)	230 (9)	95 (3.7)	95 (3.7)		
CSS Range	mm (inch)	24-35 (0.9-1.4)	26-35 (1 -1.4)	14-28 (0.6-1.1)	14-30 (0.6-1.2)		
*Capacity	TPH	140-320	160-340	120-185	150-240		
Hopper / Feeder							
Hopper Capacity	m ³	6	6	6	6		
Feed Belt Width (mm)	mm	1000	1000	1000	1000		
Main Conveyor							
Belt Width	mm	1000	1000	1000	1000		
Discharge Height	mm	3600	3600	3600	3600		
Stock Pile Capacity	m ³	69.4 @ 40°	69.4 @ 40°	69.4 @ 40°	69.4 @ 40°		
Under Carriage							
Shoe Width	mm	500	500	500	500		
Hydraulic Tank Capacity	Ltrs	390	390	390	390		
Power Unit							
Engine		Scania DC09 Engine With Alternator CAT C9.3B Engine With Alternator Cummins QSL9 Engine With Alternator.					
Diesel Tank Capacity	Ltrs	500	500	500	500		
Dimension							
Transport (L x W x H)	mm (inch)	15810X3400X4050	15810X3400X4050	15810X3400X4050	15810X3400X4050		


*Dataila may use mula acad			Madal	Unito	
**Weight	Kg (Ton)	48000(48.0)	48000(48.0)	48000(48.0)	48000(48.0)
Working (L x W x H)	mm (inch)	17815X4760X4800 (701.4X187.4X189)	17815X4760X4800 (701.4X187.4X189)	17815 x 4760 x 4800 (701.4 x 187.4 x 189.0)	17815 x 4760 x 4800 (701.4 x 187.4 x 189.0)
Transport (L x w x H)	mm (inch)	(622.4 x 133.9 x 159.4)	(622.4 x 133.9 x 159.4)	(622.4 x 133.9 x 159.4)	(622.4 x 133.9 x 159.4)


*Details may vary based on application

Note: All the above technical details may vary at any time during engineering process & design development

DIMENSIONS

Units	А	В	C
mm	17815	4760	4800
mm	17815	4760	4800
mm	17815	4760	4800
mm	17815	4760	4800
	mm mm mm	mm 17815 mm 17815 mm 17815 mm 17815	mm 17815 4760 mm 17815 4760 mm 17815 4760





GET IN TOUCH

Corporate Office: PROPEL INDUSTRIES PVT LTD SF NO : 38/1B, Trichy Main Road, Kangayampalayam, Sulur, Coimbatore - 641 401. India. **Dealer Office: Heavy Machinery Viqa,** Saih Shuaib 4,Roundabout 6 Dubai Industrial City, Dubai United Arab Emirates Communication

+971 800 MYHMV / +971 50 275 0508 Email: sales@hvmachinery.com www.hvmachinery.com

